

miniconveyor™

PLUG-N-GO



Plug-N-Go features a simple built-in On/Off switch and plugs into a standard 120V circuit.

Each Plug-N-Go requires its own 15 amp circuit to run.



Water Tight Electrical Plug

On/Off Control Switch

Portable

Our *10' x 15" Plug-N-Go weighs only 170 lbs (77kg) and can be carried into position and set up in minutes. A foam filled core sandwiched between stainless steel plates means they are structurally strong, while remaining light and durable. The units stack and lock for easy transport. All accessories, hoppers and side extensions are also constructed from weight saving material.

*Available lengths: 5' (1.5m), 10' (3m), 15' (4.5m) and 20' (6m)

*Available width: 15"

Powerful

Plug-N-Go uses powerful 370 watt motors, mounted inside the end rollers and specifically designed and manufactured in the USA for the application. Turning the belts at 80 ft/min., Plug-N-Go is the fastest conveyor in its class.

Rugged

Built for tough and demanding environments. The belt cleats are attached using high frequency welding to ensure long life. Corrosion free, all aluminum and stainless steel construction. Drive motors are sealed to IP65 standards and protected by a thermal overload circuit to guard against damage. They cannot be built any tougher.

Manufactured by:



1980 Parker Court, Suite D
Stone Mountain, GA 30087
sales@miniveyorusa.com

1-866-736-8921
T. 678-344-1165
F. 678-387-6964



Accessories



Add **Wheels** and move units effortlessly

Adjustable Leg Kits for quick set-up and adjustment. Turn corners and convey material up to 40° angle.



Side Extensions allow for moving oversized material and eliminates spillage.



Hoppers to assist in loading.



PLUG-N-GO Conveyor

Plug-N-Go has built-in ON/OFF controls and plugs directly into your 120V circuit.

Manufactured by:

Access Construction Equipment



1980 Parker Court, Suite D
Stone Mountain, GA 30087
Sales@miniveyorusa.com

1-866-736-8921
T. 678-344-1165
F. 678-387-6964

www.accessconstructionequipment.com

Plug-N-Go models	3M40P (smooth) 3M40C (cleated)
CONVEYOR	
Length	5', 10', 15' and 20'
Width	15 inches
Depth	7.5 inches
Construction	Stainless/Aluminum
Nominal Load	300 lbs
Maximum Angle* <small>load/condition dependent</small>	40 degrees
BELT	
Material	Reinforced PVC
Width	12 inches
Thickness	0.125 inches
Fastener	Stainless Wire Hook
Option Styles	MSHA & Food Grade
Standard Cleats	1" on 12" center